













Product Features

- 1080P FHD resolution, the image is more clear and delicate.
- Captures moving images without aliasing with 2 million progressive scan CMOS.
- Support AHD/TVI/CVI coaxial HD output, clear and delicate images.
- Illumination, 0.01Lux@(F1.2, AGC ON), 0LUX with IR.
- Support Warm Light.
- Support Built-in-mic.
- Support OSD menu control, suitable for user-defined settings.
- Support for digital wide dynamics.
- Adaptive digital noise reduction, 3D-DNR, 2D-DNR.
- Support for coaxial view control (UTC).
- Video 6KV lightning protection, power supply large capacitor design.
- Support DC 12V1-2A wide voltage supply.



	Model	SM-PR5028-FC
Camera Features	Image sensor	1/2.9" 2MP CMOS Sensor,
	Video output	1080P@25fps / 1080P@30fps
	PAL/NTSC	TV System
	Signal format	AHD/T VI/C VI/C VBS
	Min. Illumination	0.01Lux@(F1.2,AGC ON), OLUX with IR
	Shutter	1/50(1/60) seconds to 1/100,000 seconds
	Day/Night	Color/ B&W (IR-CUT)
Lens	Focus Length	2.8mm/F2.0
	Pixels	2MP
Night Vision	Warm LED	4PCS Warm Light
	WarmLight Distance IR	20M
	Status	Under 10 Lux By CDS
	IR Power On	CDS Auto Control
General	Material	Plastic waterproof
	UTC & Audio	Support .TVI Built-in-mic Audio
	Protect Grade	IP66
	OSD	Optional
	Language	English, Chinese Simplified, Chinese Traditional, Bulgarian,etc
	Operation	-10°C-+60°C
	Temperature Storage	10%-90% RH
	Temperature Power	DC12V±10%
	Supply Consumption	MAX 12W
	Dimensions	160(W) x62(H) x 62(D)mm
	Weight	About 500g









