

Product Features

- 1080P FHD resolution, the image is more clear and delicate.
- Captures moving images without aliasing with 2 million progressive scan CMOS.
- Support AHD/TVI/CVI coaxial HD output, clear and delicate images Illumination, 0.01Lux@(F1.2, AGC ON), 0LUX with IR.
- Support Warm Light.
- Support OSD menu control, suitable for user-defined settings Support for digital wide dynamics.
- Adaptive digital noise reduction, 3D-DNR, 2D-DNR.
- Support for coaxial view control (UTC).
- Video 6KV lightning protection, power supply large capacitor design.
- Support DC 12V1-2A wide voltage supply.













| | Model | SM-PR6322-FC |
|--------------------|-----------------------|---|
| Camera Features | Image sensor | 1/2.7" 2MP CMOS Sensor |
| | Video output | 1080P@25fps / 1080P@30fps |
| | PAL/NTSC | TV System |
| | Signal format | AHD/TVI/CVI/CVBS |
| | Min. Illumination | 0.01Lux@(F1.2,AGC ON), 0LUX with IR |
| | Shutter | 1/50(1/60) seconds to 1/100,000 seconds |
| | Day/Night | Color/ B&W (IR-CUT) |
| Lens | Focus Length | 2.8mm/F2.0 |
| | Pixels | 2MP (1920x1080) |
| Night Vision | Warm LED | 4PCS Warm Light |
| | WarmLight Distance IR | 20M |
| | IR Status | - |
| | IR Power On | - |
| General General | Material | Plastic waterproof |
| | UTC | Support |
| | Protect Grade | IP67 |
| | OSD | Optional |
| | Language | English, Chinese Simplified, Chinese Traditional, Bulgarian,etc |
| | Operation | -10°C-+60°C |
| | Temperature Storage | 10%-90% RH |
| | Temperature Power | DC12V±10% |
| | Supply Consumption | MAX 12W |
| | Dimensions | 160(W) x62(H) x 62(D)mm |
| | Weight | About 500g |









